


# LM3

Food/Steam - NBR - 6/18 bar - D - blue



## SPECIFICATIONS

### Application

LM3 is suitable for cleaning in dairies, as well for food production plants and slaughterhouses as a steam, hot water and cold water hose.  
Also for conveying liquid food stuffs, in particular milk and dairy products, animal and vegetable oils and fats.  
We don't use for the tube compound of LM3 any PHTHALATES.  
PAH we comply with requirements of EU 1907/2006 (REACH), Annex XVII Nr. 50

### Standard/Approval

BfR XXI Kat. 2, FDA [CFR 21 § 177.2600], EG1935/2004.  
REACH regulation and REACH consumer goods annex XVII

### Temperature range

-35°C / +164°C (saturated steam), +95°C (hot water).

### Safety factor

Steam 10 : 1, Hot water 3,15 : 1

### Tube

NBR, white, food quality, resistant to grease and oil, resistant to cleaning agents, smooth.

### Reinforcement

Textile wrapped.

### Cover

NVC, blue, resistant to grease and oil, cloth impression.










### Marking

continuous mylartape, white letters: "SEMPERIT (S) LM3 Lebensmittel BfR XXI Kat.2 NBR LEBENSMITTEL/DAMPF FOOD/STEAM D food quality FDA WP 6 bar 164°C Steam Made in EU".

### Notice

To meet the high demands associated with continuous steam operation we recommend DS1 ultra, DS2 or DS3 hoses.  
Very high resistance to many aggressive cleaning agents.  
For the application of cleaning agents, please refer to our separate information sheet.

# TECHNICAL DETAILS

<div></div>										
Article number	Internal-Ø		Wall width	External-Ø	Work. pressure (max.)		Number of inserts	Bending radius [min.]	Weight approx.	Coil length [max.]
	mm	inch	mm	mm	Satur. steam [bar]	Hot water [bar]		mm	kg/m	m
48244 1350	13.0	1/2	5.0	23.0	6	18	2	80	0.38	40
48244 1650	16.0	5/8	5.0	26.0	6	18	2	95	0.44	40
48244 1960	19.0	3/4	6.0	31.0	6	18	2	115	0.62	40
48244 2570	25.0	1	7.0	39.0	6	18	2	150	0.91	40
48244 3270	32.0		7.0	46.0	6	18	2	195	1.10	40
48244 3890	38.0		9.0	56.0	6	18	2	230	1.65	40
48244 4090	40.0		9.0	58.0	6	18	2	240	1.70	40
48244 5010	50.0		10.0	70.0	6	18	2	300	2.35	40
64244 6512	65.0		12.0	89.0	6	18	4	390	4.25	40
64244 7512	75.0		12.0	99.0	6	18	4	450	4.80	40
64244 8012	80.0		12.0	104.0	6	18	4	550	5.10	40
64244 0015	100.0		15.0	130.0	6	18	6	650	7.70	40

**Please note:** Before using our products with new or untested media, or for applications that are not clearly indicated in the product information, written advice must be obtained from a specialist dealer or a Semperit application engineer. For safety reasons, all products must be inspected regularly for operational safety and replaced in the event of any damage (especially of the cover) or unusual signs of wear and tear. All products must be stored, handled, and maintained in accordance with all our respective instructions and DIN 7716:1982. The information in our catalogue as well as each individual datasheet is subject to change at any time without notice since we are constantly developing and improving our products and due to constant technical developments after the latest release date of the catalogue and/or individual datasheets. To always have the latest product and safety information make sure you visit our website ([hoses.semperitgroup.com](https://hoses.semperitgroup.com)) regularly or contact one of our specialist dealers or a Semperit application engineer. All contracts concluded with us are exclusively subject to our general terms and conditions (available at [semperitgroup.com](https://semperitgroup.com)). Additional important general information about the range, choice and safe use of our products can be found at our website ([hoses.semperitgroup.com](https://hoses.semperitgroup.com)) and must be followed without exception.

**Important notice:** Our catalogue and any individual datasheet have been prepared with great care in order to provide you with all the information you need. The information contained therein is based on the state-of-the-art industrial technology and many years of experience and testing; whenever indicated for a certain product, we also confirm conformity with the resistance requirements of the media listed in ISO TR 7620:2005(E). However, the individual conditions of storage, maintenance and use decisively affect the safe and durable use of each product. The quality and safety of our products as indicated in the catalogue or individual datasheets are therefore strictly subject to your continuous observance of all specifications and restrictions in our written product information and applicable laws and standards, the specifications regarding resistance to chemicals and our cleaning procedures. We reject any liability for safety issues or other consequences due to improper product choice, maintenance, or handling (e.g. squashing, rupturing, stretching, or filling with non-approved media). Our products must not be used in airplanes or other aerial vehicles under any circumstance. Products delivered by us to the USA are manufactured according to IRPM-IP2, unless specified otherwise. All other hoses are manufactured according to EN ISO 1307:2008, unless specified otherwise. Our products are not designated for the sale to the general public and do not fulfill the conditions for "GS-certification", unless stated otherwise in the product datasheet.